



The primary purpose of clay treatment is to protect aviation fuel filtration systems and jet fuel by removing trace quantities of surfactants (surface active agents), color and additives commonly found in fuel.

Facet's specially selected Attapulgus clay greatly resists water saturation and provides maximum surfactant absorptivity and filtration area found in clay treater cartridges.

STANDARD DESIGN FEATURES

- Maximum adsorptive and filtration area
- Greatly resists water saturation
- Vibra-packed clay minimizes settling
- Interchangeable with other manufacturer's bag and canister clay treater cartridges
- Hoisting handles expedite cartridge installation and changeout
- Flow direction: Outside to in

MATERIALS

Bag Cartridge

- Polypropylene center tube
- Felt center tube migration barrier
- Tightly woven canvas bag
- Vibra-packed with Attapulgus clay to capacity
- Heavy-duty canvas hoisting handles

Canister Cartridge

- Perforated metal center tube
- Non-woven polyester inner migration barrier
- Vibra-packed with Attapulgus clay to capacity
- Heavy-duty metal hoisting handle
- Reinforced Plastic Endcaps
- Polyester outer wrap
- Buna-N gaskets on both ends for assured sealing

DATA

MODEL NUMBER	TYPE	RECOMMENDED FLOW RATE PER CARTRIDGE		MEDIA	DIMENSIONS						MAXIMUM OPERATING TEMPERATURE	
		gpm	lpm		NOMINAL LENGTH		OUTSIDE DIAMETER		INSIDE DIAMETER		°F	°C
					in.	mm.	in.	mm.	in.	mm.		
C-766-4	Canister	5-7	19-27	Attapulgus clay, low	18	460	7	177	2¼	57	240	115
C-727-6	Bag	5-7	19-27	Volatile material	18	460	7	177	2¼	57	140	60
C-727-2	Bag	5-7	19-27	Graded 60-90 mesh	19	480	7	177	2¼	57	140	60