



STANDARD DESIGN FEATURES

- Meet EI 1583 effluent requirements
- Maximum pressure rating: 50 psi
- Removes free and emulsified water
- All metal components are treated against corrosion
- Gaskets are Buna-N

Facet's Fuel-Gard® Aviation Spin-On Filters perform three jobs to give you clean, dry fuel. They absorb free and emulsified water, remove ultra-fine solids even when surfactants and fuel additives are present, and shut down system flow when hit with a localized slug of water. The filters are designed to flow at a rate of 13 gpm (FGS-O-405) and 15 gpm (FGS-O-409).

DATA

MODEL	DIAMETER	LENGTH	THREAD	WEIGHT	VELCON REPLACEMENT
FGS-O-405	3¾"	5½"	1" - 12 NF	1¼ lbs.	ACO-40501SPK
FGS-O-409	3¾"	8½"	1⅜" - 12 NF	1½ lbs.	ACO-40901SPK

WARNING: MONITOR CARTRIDGES SHOULD NEVER BE USED WITH FUELS CONTAINING ANTHCING ADDITIVES SUCH AS FSII, PRIST AND DIGME. THIS INCLUDES PRE-MIXED AND MILITARY FUELS CONTAINING THESE ADDITIVES. THE USE OF MONITOR CARTRIDGES WITH FUELS CONTAINING ANTHCING ADDITIVES MAY RESULT IN (1) A FAILURE OF THE MONITOR CARTRIDGE AND/OR (2) MIGRATION OF FILTRATION MEDIA INTO THE FUEL STREAM, EITHER OF WHICH COULD POTENTIALLY CAUSE DAMAGE TO OR SUDDEN FAILURE OF THE CORRESPONDING ENGINE. THE SUPPLIER SHALL NOT BE LIABLE IN ANY RESPECT FOR ANY DAMAGE OR LOSS THAT ARISES FROM THE USE OF MONITOR CARTRIDGES WITH FUELS CONTAINING ANTHCING ADDITIVES. SUCH USE IS ENTIRELY AT THE USER'S RISK.