



FOR MAXIMUM WATER COALESCING EFFICIENCY AND SOLIDS HOLDING CAPACITY

Facet CM100 Series coalescer cartridges offer the finest performance available. This line of high flow coalescer cartridges removes ultra-fine solids and enhances separation of water from jet fuel.

The Facet coalescer separator housings equipped with CM100 Series coalescer and companion separator cartridges have been tested and fully qualified to EI 1581, Fifth Edition, for category "M100", in both vertical and horizontal orientations.

Built for balanced fluid flow-thru and structural strength, each CM100 Series coalescer cartridge is a single piece construction of various combined media, precisely arranged in many layers and pleats, wrapped around a coated, perforated metal center tube- all encased in an outer sock material. All are 6" OD (152mm) by 3.5" ID (89mm) and available in standard interchangeable nominal lengths in increments from 11.25" (290mm) to 57.25" (1450mm).

The CM100 Series 5 coalescer cartridges are available in two cartridge mounting styles; self-centering rod mount and screw base. The rod mount style has treated metal end caps, while the screw base ends are injection molded, glass-filled nylon. This screw base material offers superior strength and ease of maintenance- uniform threads, no shrinkage, no galling and no gasket recover.

A permanently affixed Buna gasket seals against the V-type knife edge mounting adaptor to provide a positive seal. It will not separate from the cartridge during installation or change out.

STANDARD DESIGN FEATURES

- Tested and qualified to the Fifth Edition of EI 1581 for all category "M"
- Multi-layered media for increased solids holding capacity
- Ultra-fine solids removal
- Maximum water coalescence
- Balanced cartridge flow characteristics
- Recommended maximum operating temperature: 240°F (115°C)
- Withstands excess of 75 psi differential pressure
- pH range from 5 to 9
- Choice of self-centering rod or screw base coalescer cartridge mounting styles

MATERIALS

- All metal components are treated against corrosion
- Screw base ends are injection molded, glass-filled nylon with locked-in gaskets
- Buna-N gaskets-other materials are available upon request
- Buna-N gaskets-other materials are available upon request

DATA

MODEL NUMBER	NOMINAL LENGTH (IN)	NOMINAL LENGTH (MM)	OUTSIDE DIAMETER OD (IN)	INSIDE DIAMETER ID (IN)	MOUNTING STYLE
CM100-11-5	11¼	290	6	3½	Rod
CM100-14-5	14½	370	6	3½	Rod
CM100-14SB-5	15	380	6	3½	Screw Base
CM100-22-5	22¼	560	6	3½	Rod
CM100-22SB-5	23	580	6	3½	Screw Base
CM100-28-5	28¾	730	6	3½	Rod
CM100-28SB-5	29	740	6	3½	Screw Base
CM100-33-5	33¼	840	6	3½	Rod
CM100-33SB-5	34	860	6	3½	Screw Base
CM100-38-5	38	960	6	3½	Rod
CM100-38SB-5	39	990	6	3½	Screw Base
CM100-43-5	43¼	1100	6	3½	Rod
CM100-43SB-5	45	1140	6	3½	Screw Base
CM100-56-5	56¼	1430	6	3½	Rod
CM100-56SB-5	57	1450	6	3½	Screw Base

NOTE: The Facet screw base adaptor part number is 677453A-AM.